



LTX-800

Morooka Custom Tool Carriers

Manufactured in USA

Performance	
Max. Carrying Capacity	12,000 lbs.
Travel Speed - 1st Gear	5.1 mph
Travel Speed - 2nd Gear	7.5 mph
Gradeability (unloaded)	30 degrees
Turning Radius	7' 9"
Ground Pressure	2.3 psi
Ground Pressure (loaded)	3.8 psi



Dimensions—Base Unit	
Full Length	16' (opt.)
Full Width	7' 7" (opt.)
Wheel Base	10' 3"
Min. Ground Clearance	18"
Front Overhang	3' 6"
Gauge	5' 7" (opt.)
Track Width	23"
Full Height	7' 10"
Dumping Angle	58 deg.
Machine Weight	12,500 lbs.

Engine
Make: Deere
Model: 4045T
4 cylinders
Displacement: 4.5 liters
115 hp @ 2,400 rpm
Fuel tank capacity: 27.7 gal.

Other Models; Quick Spec. Chart

Model	Weight	Load	Horsepower
MST300VD/R	5,000 lbs.	5,000 lbs.	46 hp
MST600VD	8,800 lbs.	7,260 lbs.	76 hp
MST1500VD	20,282 lbs.	13,892 lbs.	204 hp
MST2200VD	29,762 lbs.	22,050 lbs.	250 hp
LTX3500	42,000 lbs.	35,000 lbs.	475 hp

For more information, contact your local dealer: Equipment Direct, Inc. www.eqdirect.com
 Toll Free: 1-866-748-5195 Business: 1-907-696-5001 After Hours: 1-907-952-2740