



MST-2200VD Morooka Rubber Track Carriers

Performance	
Max. Carrying Capacity	22,046 lbs.
Travel Speed - 1st Gear	0 - 5.0 mph
Travel Speed - 2nd Gear	0 - 7.5 mph
Gradeability (unloaded)	30 degrees
Turning Radius	11' 5"
Ground Pressure	3.1 psi
Ground Pressure (loaded)	5.7 psi



Dimensions	
Full Length	19' 7"
Full Width	9' 6"
Wheel Base	12' 7"
Min. Ground Clearance	17"
Front Overhang	4' 2"
Gauge	6' 9"
Track Width	29"
Track Length	32' 5"
Full Height	10' 4"
Height of Dump Bed	4' 9"
Height of Dump Side	1' 4"
Length of Dump Bed	11' 10"
Width of Dump Bed	8' 1"
Dumping Angle	60 degrees
Machine Weight	29,762 lbs.

Engine
Make: CAT
Model: C7
6 cylinders
Displacement: 7.24 liters
250 hp @ 2,100 rpm
Fuel tank capacity: 63.4 gal.

Other Models; Quick Spec. Chart

Model	Weight	Load	Horsepower
MST300VD/R	5,000 lbs.	5,000 lbs.	46 hp
MST600VD	8,800 lbs.	7,260 lbs.	76 hp
MST800VD	14,200 lbs.	9,482 lbs.	115 hp / 129 hp
MST1500VD	20,282 lbs.	13,892 lbs.	204 hp / 225 hp