



MST-600VD/L Morooka Rubber Track Carriers

Performance	
Max. Carrying Capacity	7,260 lbs.
Travel Speed - 1st Gear	4.7 mpg
Travel Speed - 2nd Gear	7.5 mph
Gradeability (unloaded)	30 deg.
Turning Radius	96"
Ground Pressure	7.2 psi
Ground Pressure (loaded)	3.6 psi



Dimensions	
Full Length	150"/180"
Full Width	77"
Wheel Base	96"
Min. Ground Clearance	14"
Front Overhang	25"/38"
Gauge	57"
Track Width	20"
Full Height	90"
Height of Dump Bed	44"
Height of Dump Side	14"
Length of Dump Bed	85"
Width of Dump Bed	67"
Dumping Angle	60°
Machine Weight	8,800 lbs.

Engine
Make: Kubota
Model: V3307
4 cylinders
Displacement: 3 liter
76 hp @ 2,150 rpm
Fuel tank capacity: 22 gal.

Other Models; Quick Spec. Chart

Model	Weight	Load	Horsepower
MST300VD/R	5,000 lbs.	5,000 lbs.	46 hp
MST800VD	14,200 lbs.	9,482 lbs.	115 hp / 129 hp
MST1500VD	20,282 lbs.	13,892 lbs.	204 hp / 225 hp
MST2200VD	29,762 lbs.	22,050 lbs.	250 hp